DIGITAL MULTIMETER
METEX M-3800

Features

- 3½ Digit, Automatic Polarity Indication
- Voltage and Current AC/DC
- Resistance
- hFe Test
- Continuity Test

Specification

	Range	Resolution	Accuracy
DC V	200mV – 1000V	100µV – 1V	+ 0.5% + 1d
AC V	200mV – 750V	100µV – 1V	+ 0.8% + 3d
DC A	20µA – 20A	0.1µA – 10mA	+ 1.2% + 1d
AC A	20µA – 20A	0.1µA – 10mA	+ 1.8% + 3d
Resistance	200Ω - 20MΩ	0.1Ω - 10kΩ	+ 0.5% + 2d
Transistor (hfe) Test			
Continuity test			
Input Impedance	10MΩ		

Information	Dimensions	88 mm (W) x 172 mm (L) x 36 mm (H)
	Display	LCD 57 x 23 mm
	Weight	340 + 10 g (with battery)
	Accessories	Instruction manual, Test leads, Carrying case, 9V battery, Spare fuse

GLOBAL FOCUS Ltd.
1119 Budapest, Etele str. 59-61.
Hungary
Tel: +36 1 481-1233, +36 1 481-1231, +36 1 481-1161, +36 1 481-1162
Fax: +36 1 203-4355
E-mail: gmark@mta.mmsz.hu