

# HY425: Computer Systems Architecture

**Homework Problem Set 1**  
**Assignment: Friday 03/10/2014**  
**Due: Monday 13/10/2014 23:59:59**

**Instructions:** Solve all problems in a single .pdf file and send them via e-mail to Vaggelis Vasilakis (vvasil@csd.uoc.gr). Use the subject: **HY425 - Homework 1**

## Problem 1 (30 points)

For this problem you will need a spreadsheet. The following table illustrates the performance of several processors using two benchmarks. The first benchmark stresses the memory system (how fast can the memory system respond to loads and stores), whereas the second benchmark, Dhrystone, stresses the execution units of the processor.

Chip	#Cores	Frequency (MHz)	Memory Performance	Dhrystone Performance
Athlon 64 X2 4800+	2	2400	3623	21818
Pentium EE 840	2	2200	3228	19993
Pentium D 820	2	3000	3005	15320
Athlon 64 X2 3800+	2	3200	2841	17529
Pentium 4	1	2800	2831	8821
Athlon 64 3000+	1	1800	2643	7978
Pentium 4 570	1	2800	3610	11210
Processor X	1	3000	6500	6150

- i. Create a table similar to the one above, except express the results as normalized to the slowest processor (in terms of frequency) for each benchmark. Notice that performance is reported as a rate (a-la SPEC).
- ii. Calculate the arithmetic mean of the performance of each processor. Use both the original performance and your normalized performance calculated in part (i). Which processor achieves the highest score in each case?
- iii. Calculate the geometric mean of the normalized performance of the dual-core processors and the geometric mean of the normalized performance of the single-core processors for the memory benchmark.
- iv. Which processor would you choose if you intended to run an application which spends **75%** of its time on memory-bound computations and **25%** on compute-bound computations?

## Problem 2 (20 points)

Your company has just bought a new system with a dual-core processor, and you have been tasked with optimizing your software for this system. You will run two applications on this dual-core machine, but the resource requirements are not equal. The first application needs **80%** of the resources, and the other only **20%** of the resources.

- i. Given that **30%** of the first application is parallelizable, how much speedup would you achieve with that application if run in isolation?
- ii. Given that **80%** of the second application is parallelizable, how much speedup would this application observe if run in isolation?
- iii. Given that **30%** of the first application is parallelizable, how much overall system speedup would you observe if you parallelized it, but not the second application?
- iv. How much overall system speedup would you achieve if you parallelized both applications, given the information in parts (i) and (ii)?

## Problem 3 (30 points)

Your company's internal studies show that a single core system is sufficient for the demand on your processing power. You are exploring, however, whether you could save power by using (a) two or (b) four or (c) eight cores.

- i. Assume your application is **70%** parallelizable. By how much could you decrease the frequency and get the same performance in each case (a,b,c) ?
- ii. Assume that the voltage may be decreased linearly with the frequency. How much dynamic power would each system require as compared to the single- core system? For the capacitive load  $C$  of the multi-core systems assume that:  $C(N) = C(1) \times \text{SQRT}(N)$ .
- iii. Now assume that the voltage may not decrease below **30%** of the original voltage. This voltage is referred to as the "voltage floor," and any voltage lower than that will lose the state. What percent of parallelization gives you a voltage at the voltage floor for each case?
- iv. How much dynamic power would each system require as compared to the single-core system when taking into account the voltage floor? For the capacitive load  $C$  of the multi-core systems assume that:  $C(N) = C(1) \times \text{SQRT}(N)$ .

## Problem 4 (20 points)

A hypothetical supercomputer has as many as **131072** processors. The processors are organized in **131072** node cards, where each node has one off-chip DRAM memory module and a hard disk. The system administrator of this supercomputer claims that, on average, he loses one node per four days due to processor failures, a node per six days, due to memory failures, and a disk per forty

days due to disk failure. Assume that the three types of failures are not related.

**i.** What is the **MTTF** of each processor, memory module and disk on the supercomputer?

**ii.** What is the **MTTF** of the system as a whole?

**iii.** If each failure requires replacement and reboot of a node on the supercomputer, and this process takes 2 hours, what is the availability of the supercomputer?