Lecture 6: The Untyped Lambda Calculus

Semantics and Implementation

Polyvios Pratikakis

Computer Science Department, University of Crete

Type Systems and Static Analysis

Last class

- Lambda calculus, cf.1930s
  - Simple, core language: everything is a function
  - Can express all computation
  - Can encode complex language features as syntactic sugar
  - Simple semantics, one instruction: function application

Defined in one slide

- Syntax:

$$
\begin{array}{rcll}
e & ::= & x & \text{Variables} \\
 & | & \lambda x.e & \text{Function definition} \\
 & | & e\ e & \text{Function application}
\end{array}
$$

- Nondeterministic small-step semantics:

$$
\frac{}{(\lambda x.e_1)\ e_2 \to e_1[x \mapsto e_2]}
\qquad
\frac{e \to e'}{(\lambda x.e) \to (\lambda x.e')}
$$

$$
\frac{e_1 \to e_1'}{e_1\ e_2 \to e_1'\ e_2}
\qquad
\frac{e_2 \to e_2'}{e_1\ e_2 \to e_1\ e_2'}
$$

Fun with encodings

- Church integers: $\lambda s.\lambda z.\langle \text{apply } s \text{ on } z \text{ for } n \text{ times} \rangle$
- Booleans: true $= \lambda t.\lambda f.t$ and false $= \lambda t.\lambda f.f$
- Pairs: $(a, b) = \lambda p.p\ a\ b$
- In general, encode data as a function that takes an action, and applies it on the data
- How about lists?
  - $[] = \lambda f.\lambda n.n$
  - $a :: b = \lambda a.\lambda b.\lambda f.\lambda n.f\ a\ (b\ f\ n)$
- Examples:
  - Predecessor function
  - Addition and subtraction
  - Check a list for empty
  - Head and tail function for lists

Example: Predecessor function for ints

- We want pred 0 to evaluate to 0, pred 1 to 0, pred 2 to 1, etc.
- Remove one application of s from the chain $s(s(s \ldots (s\ z)$
- Unfortunately not very easy for Church integers
- Solution: rebuild the given number up to the previous number
  - Similar to encoding of integers: base, inductive case
  - Use pairs of predecessor, number: $(\text{pred}\ n, n)$
  - Base case, or "zero"—start with pred 0, which is 0:
    - ★ $zz = (0, 0)$
  - Inductive case, or "successor"—construct the next pair $(n, \text{succ}\ n)$ from the previous $(\text{pred}\ n, n)$
    - ★ $ss = \lambda p.(\text{snd}\ p, (\text{succ}\ (\text{snd}\ p))$
  - pred m is the first item of the m-th pair
    - ★ $\text{pred}\ = \lambda m.(\text{fst}\ (m\ ss\ zz))$

Example: plus and minus

- Plus: given two numbers m and n, construct a number $m + n$
  - Replace zero in m with n: plus $= \lambda m.\lambda n.\lambda s.\lambda z.n\ s\ (m\ s\ z)$
- Minus is a bit more complex
- $m - n$: apply pred on m, n times
  - But, n takes a function s and a z and applies s on z for n times
  - Just call it with $s =$ pred , and $z = m$:
  - minus $= \lambda m.\lambda n.n$ pred m
  - Will apply pred on m for n times: $m - n$

Terminology reminder

- *Combinator*, or *closed term*: a term with no free variables
- *Normal form*: a term that cannot be reduced further
  - Normal form of a term is unique
  - Does not always exist, a term may run forever
  - Is not always reached, depending on evaluation order
- A *redex* is a subterm that can be reduced: $(\lambda x.e)\ e'$
- Equivalent terms *up to α-conversion*: they can be made equal by renaming bound variables
- Substitution $e[e'/x]$ or $e[x \mapsto e']$: replace all occurences of x in e by e'.
  - *Capture-avoiding*: e' does not have free variables that become bound because of substitution
  - Always possible, using α-conversion to rename variables

Evaluation strategies

- Full β-reduction: nondeterministic semantics
- Normal order: always reduce leftmost, outermost redex
- Call-by-name (*lazy*): no reductions under λ, only at the top-level
  - Call-by-need (used in haskell): remember term substitutions and replace all copies of an evaluated term in the AST with the value
  - Instead of AST: abstract syntax *graph*
- Call-by-value (*eager*): reduce only outermost redexes where the argument is a value

Lazy semantics

- Small-step:

$$\frac{}{(\lambda x.e_1)\ e_2 \to e_1[x \mapsto e_2]} \qquad \frac{e_1 \to e_1'}{e_1\ e_2 \to e_1'\ e_2}$$

- Big-step:

$$\frac{}{(\lambda x.e) \downarrow (\lambda x.e)} \qquad \frac{e_1 \downarrow (\lambda x.e) \qquad e[x \mapsto e_2] \downarrow e'}{e_1\ e_2 \downarrow e'}$$

Eager semantics

- Define values as:

$$v \quad ::= \quad \lambda x.e$$

- Small-step:

$$\frac{e_1 \to e_1'}{e_1\ e_2 \to e_1'\ e_2} \qquad \frac{e_2 \to e_2'}{v\ e_2 \to v\ e_2'} \qquad \frac{}{(\lambda x.e)\ \ v \to e[x \mapsto v]}$$

- Big-step:

$$\frac{}{(\lambda x.e) \downarrow (\lambda x.e)} \qquad \frac{e_1 \downarrow (\lambda x.e) \qquad e_2 \downarrow v_2 \qquad e[x \mapsto v_2] \downarrow v}{e_1\ e_2 \downarrow v}$$

In code

- All so far is syntax driven: look at the syntax, decide which rule to apply
- The same for all helper function definitions: $FV(e)$, $subst(e, x, e')$, etc.
- OCaml datatypes and pattern matching helps with that
- The abstract syntax tree:

```
type exp =
    Var of string
  | Fun of string * exp
  | App of exp * exp
```

e	$::=$		Expessions
		x	Variables
	$\mid$	$\lambda x.e$	Function definition
	$\mid$	$e\ e$	Function application