Image Completion Using Global Optimization

Nikos Komodakis and Georgios Tziritas

University of Crete, Computer Science Department, E-mail: {komod,tziritas}@csd.uoc.gr



The image completion problem


□ Fill missing part of an incomplete image in a visually plausible way



☐ We want to be able to handle:

- complex natural images,
- with a (possibly) large missing region
- and all these in an automatic way (i.e. no user intervention)

☐ We also want our method to be able to handle the related problems of texture synthesis and image inpainting



Related methods

□ Statistical-based: they use parametric statistical models for textures (mostly suitable for synthesis of stochastic textures)

□PDE-based: they fill region through a diffusion process, simulated by a non-linear PDE (suitable for thin & smooth missing regions)

□Exemplar-based: they fill by copying patches from observed part (very good at texture synthesis but may lead to bad completions due to greedy decisions)

Contributions to image completion

 \Box A new exemplar-based framework is proposed that unifies image completion, texture synthesis and image inpainting

☐ All these tasks are posed as discrete MRF optimization problems with a well-defined energy (but with a huge number of labels)

□ Completion is solved in a global way (i.e. no greedy decisions)

□ Our method is fully automatic and does not rely on any image specific prior knowledge (i.e. it can be applied to any image)

Contributions to MRF optimization

□ A novel MRF optimization scheme, called "Priority-BP", is proposed that can handle discrete MRFs with a huge number of labels.

□ Priority-BP carries 2 extensions over standard Belief Propagation: "Dynamic label pruning" and


"Priority-based message scheduling"

☐ Generic method for efficiently applying Belief Propagation to MRFs with very large discrete state-spaces

(it thus resolves one of the main limitations of Belief Propagation)

□ Priority-BP is generic (i.e. it can be applied to any MRF)


Completion as MRF optimization



Labels L = all wxh patches from S (a huge number!)

MRF nodes = all lattice points whose wxh neighborhood intersects target region T

singleton potential $V_p(x_p) = \text{how well source}$ patch x_p agrees with source region around p pairwise potential $V_{pq}(x_p, x_q) = how well |$ source patches x_p, x_q agree on their overlap after placing them above p and q




E.g. $V_r(x_r)$ =match over red region , $V_{pq}(x_p,x_q)$ =match over green region


Completion then reduces to optimizing the following MRF energy: $\sum_{p} V_p(x_p) + \sum_{(p,q)\in E} V_{pq}(x_p, x_q)$


Intuitively, one can think of it as trying to solve a huge jigsaw puzzle.


Belief Propagation (BP)

□ BP is an MRF optimization technique, which is based on the idea of propagating local messages along the nodes of an MRF











Priority-BP

□ In our case, BP has an intolerable computational cost:

just the basic operation of sending messages from p to q requires $|L|^2$ patch comparisons (recall that |L| is huge!)

☐ To fix that, Priority-BP carries 2 important extensions over BP:

• "Dynamic label pruning" and "Priority-based message scheduling"

☐ Resolves one of the main limitations of BP: • Its inefficiency to handle MRFS with a huge number of labels

 Active research topic, but existing methods apply only to restricted class of MRFs, e.g. see [Felzenswalb04]

• On the contrary, our method is generic (i.e. applicable to any MRF)

☐ Priority-BP is based on the following key-idea:

- It tries to drastically reduce the number of labels
- But instead of pruning the labels beforehand, this is done on the fly
- To this end, it makes use of information carried only by BP itself (this ensures that the algorithm will be generic)

Priority-based message scheduling

□Not all MRF nodes are equally adequate for pruning

e.g. node **a** is very inappropriate for pruning, whereas node c can tolerate a lot of pruning



And then apply the following scheduling to messages:

Message scheduling principle: the most "confident" nodes transmit their messages first, i.e. they have higher priority


☐ The above scheduling is good for the following reasons:

- The more confident a node, the more pruning it can tolerate. But recall, message from non-pruned node costs: O(|L|) time whereas, message from pruned node is cheap: O(|Lpruned|) time (only cheap messages thus circulate in the network)
- Confident nodes help their neighbors to increase their own confidence (even more pruning is thus possible)
- Informative messages are propagated first (convergence of BP is accelerated)

Forward/Backward message pass

☐ To ensure that messages across all nodes get transmitted at each iteration, we divide each iteration into a forward & backward pass:

☐ Message scheduling and pruning takes place only during the forward pass (half of the messages get transmitted here)



 \Box At forward pass, we visit nodes by priority. A visited node (e.g. p) sends messages to its unvisited neighbors only (e.g. q and r)

□ Backward pass just ensures that the other half of the messages gets transmitted as well

Assigning priorities to nodes

☐ Obviously, priority should be proportional to confidence. But how can we define confidence in a generic way?

 \square Key idea: use set of beliefs $\{b_{\scriptscriptstyle D}(x_{\scriptscriptstyle D})\}$ calculated by BP for each node p

 \square For each node p, define its confusion set $\mathbb{CS}(p)$ containing the labels with high (relative) belief at that node:

 $\mathbb{CS}(p) = \{x_p \in L : b_p^{\mathrm{rel}}(x_p) \ge b_{\mathrm{conf}}\}$


 \square Priority of p then defined as: priority $(p) = 1/|\mathbb{CS}(p)|$ (other entropy-like measures have been tested as well)

Applying Priority-BP to completion

□ Novel use of confidence in image completion: we use it to decide the order of message passing and not for greedily choosing which patch to

□ Also, confidence definition is generic (no image heuristics involved)

□ Algorithm learns by itself to propagate first the messages of the nodes containing salient image structure




In the above plots, the beliefs for labels in the confusion set of a node are plotted in red. These plots illustrate how priority is defined for nodes \mathbf{a} , \mathbf{b} and \mathbf{c} at the beginning.

Dynamic label pruning


☐ What criterion should we use for label pruning? Moreover, how can this criterion be generic as well?

☐ We will again make use of the beliefs calculated by the algorithm: Active labels will be only those whose belief is high (i.e. belief exceeds a certain threshold, say b_{prune}).

☐ To discard very similar patches, an additional filtering of active labels is also needed (alternatively, texton clustering can be used [malik01])







Extensions


□ Completion by energy refinement: one may refine completion simply by refining (i.e. adding terms to) the energy function E.g., to favor spatial coherence, one may add the following terms:

$$V_{pq}^{0}(x_{p},x_{q}) = egin{cases} w_{0} & ext{if } x_{p}-x_{q}
eq p-q \ 0 & otherwise \end{cases}$$


□ Multiscale image completion: use completion at coarse scale to compute singleton-potentials at next finer scale (Features at multiple scales can thus be captured).

Further results

I. Object Removal



II. Texture synthesis



III. Image inpainting







IV. Text removal

